

LED Track Light Spotlight LED Ceiling Spotlight Adjustable LED Spotlight Gooseneck Track Light Dimmable Accent Lighting with Zoomable Beam

Flexible directional spotlight with a zoomable beam, precise aiming, and track or ceiling mounting

This adjustable LED spotlight is designed for modern spaces where lighting must be both functional and visually refined. Its slim cylindrical head, flexible arm, and minimalist mounting options support ceiling or 1-phase track installation.

The optical focus lens offers selectable 15°, 20°, 35°, or 45° beam settings for precise accent lighting or broader illumination. Available 3000K, 4000K, and 6000K options suit residential, gallery, retail, office, and hospitality applications.



7W / 10W / 15W - Track or Ceiling Mount

ZOOMABLE BEAM

FLEXIBLE ARM

TRACK / CEILING

KEY PRODUCT DATA

POWER OPTIONS

7W / 10W / 15W

Three power options

BEAM ANGLE

15° - 45°

Zoomable optical beam

MOUNTING

TRACK / CEILING

Two installation formats

MATERIAL

ALUMINUM

Durable metal body

CCT OPTIONS

3000K / 4000K / 6000K

Warm / neutral / cool

INPUT VOLTAGE

AC 110-240V

Wide-voltage supply

AVAILABLE CONFIGURATIONS

FINISH

Black

DIMMING

Non-dimmable

ADJUSTABILITY

360° / 90° tilt

LENS

Optical focus

PRODUCT INFORMATION

Technical Specification

PRODUCT SPECIFICATIONS

Feature	Details
Product Type	Adjustable LED track / ceiling spotlight
Installation Options	Track mount or ceiling mount
Body Material	Aluminum
Finish Color	Black
Light Source	Integrated LED
Available Wattages	7W / 10W / 15W
Beam Angle Options	15° / 20° / 35° / 45° - adjustable
Adjustability	Flexible arm + rotatable directional head
Color Temperature	3000K / 4000K / 6000K
Input Voltage	AC 110-240V
Dimming	Non-dimmable - verify selected version
Lens Type	Optical focus lens
Track Mount	1-phase, 2-wire track base
Applications	Living, gallery, retail, office, hospitality

COMPACT DIMENSIONS



41 mm head; 96 mm body; 290 mm arm; 64 mm base.

ZOOMABLE BEAM



Selectable 15°, 20°, 35°, or 45° beam settings.

COLOR TEMPERATURE



3000K, 4000K, and 6000K output options.

PRODUCT NOTES

- **Mounting formats:** Select the 1-phase 2-wire track adapter or the round ceiling base to suit the installation.
- **Size families:** Supplied graphics show a compact 41 x 96 mm head with a 290 mm arm, and an extended 54 x 182 mm head with a 485 mm arm. Verify the ordered model.
- **Dimming verification:** The supplied title mentions dimmable accent lighting, while the detailed specification lists non-dimmable. Confirm the required version before ordering or connecting a dimmer.

FLEXIBLE DIRECTIONAL ACCENT LIGHTING

RETAIL / RESIDENTIAL / DISPLAY APPLICATIONS

Design and Installation



RECOMMENDED INSTALLATION SEQUENCE

1

Isolate the circuit and confirm AC 110-240V, selected wattage, and mounting format.

2

Secure the track adapter or ceiling base to a stable support and provide wiring access.

3

Complete the line and neutral connection following the instructions supplied with the selected model.

4

Restore power, bend and aim the arm, then adjust the optical beam from 15° to 45°.



DESIGN GUIDANCE

- **Aiming:** Use the flexible arm with directional rotation and up to 90° tilt for precise placement.
- **Beam:** Select 15° or 20° for focused accents; use 35° or 45° for broader coverage.
- **CCT:** 3000K for warm ambiance, 4000K for neutral task light, and 6000K for crisp cool light.
- **Track:** Use the supplied 1-phase 2-wire track base only with a compatible track system.
- **Controls:** Do not connect to a dimmer unless the delivered model is specifically identified as dimmable.

Verify the delivered model, voltage, mount, dimensions, wattage and supplied hardware before installation. Use a qualified installer.

PROJECT SELECTION GUIDE

Specification and Selection

PRODUCT DESCRIPTION

The Adjustable LED Track / Ceiling Spotlight combines a slim cylindrical head, flexible gooseneck arm, and an optical focus lens for precise accent illumination. Selectable 15°, 20°, 35°, and 45° beam settings allow the light to move from tight highlighting to broader coverage. Track and ceiling mounting options, 7W / 10W / 15W power choices, AC 110-240V input, and 3000K / 4000K / 6000K color temperatures support living spaces, galleries, retail displays, offices, and hospitality interiors.



PROJECT SELECTION GUIDE

PRODUCT	Adjustable LED track / ceiling spotlight with zoomable beam
POWER OPTIONS	7W / 10W / 15W
INPUT VOLTAGE	AC 110-240V
MOUNTING	Track mount or ceiling mount
MATERIAL	Aluminum
FINISH	Black
LIGHT SOURCE	Integrated LED
BEAM ANGLES	15° / 20° / 35° / 45° - adjustable
AIMING	Flexible arm / 360° rotation / 90° tilt
CCT	3000K / 4000K / 6000K
DIMMING	Detailed specification: non-dimmable; verify version
COMPACT SIZE	Head Ø41 x 96 mm; arm 290 mm; base Ø64 x 28 mm
EXTENDED 15W	Head Ø54 x 182 mm; arm 485 mm
TRACK BASE	1-phase 2-wire; approx. 93 x 25 mm
APPLICATION	Living / gallery / retail / office / hospitality / display

Confirm the exact mount, dimensions, wattage, CCT, beam setting and dimming status before final issue or installation.